



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER JIS H3250 C3604BD.
2. NICKEL PL. 100 MIN. OVER COPPER PL. 50 MIN.
3. GOLD PL. 3 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	PART NO.
4	FERRULE	NOTE 1	NOTE 2	1	FERRULE-316
3	CONTACT PIN	NOTE 1	NOTE 3	1	FME11-316-3
2	INSULATOR	TFEON		1	FME11-316-2
1	BODY	NOTE 1	NOTE 2	1	FME11-316-1

DIMENSION ARE MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES
1-10 = ±0.2
10-30 = ±0.4
30-200 = ±1.5
200-1000 = ±10
1000-~ = ±25

SCALE	4 / 1	REV	-	UNIT	M/M
TITLE	FME CABLE RG/174U RG/316U CRIMP PLUG				
DRAWING NO.	FME11H-316				

	CHECKED	DATE
	09/08/2005	09/08/2005
DRAWN	DATE	
	09/08/2005	