



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER JIS H3250 C3604 BD.
2. INSULATOR: PTFE ASTM-D-1457.
3. GOLD PL. 3 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	PART NO.
6	HEX NUT	NOTE 1	NOTE 3	1	BNC43-5
5	WASHER	NOTE 1	NOTE 3	1	BNC43-4
4	FERRULE	NOTE 1	NOTE 3	1	N45-316-5
3	CONTACT PIN	NOTE 1	NOTE 3	1	FME15-179-3
2	INSULATOR	NOTE 2		1	FME15-179-2
1	BODY	NOTE 1	NOTE 3	1	FME15G-179-1

DIMENSION ARE MILLIMETERS  
UNLESS OTHERWISE SPECIFIED  
TOLERANCES

1-10 =  $\pm 0.2$   
10-30 =  $\pm 0.4$   
30-200 =  $\pm 1.5$   
200-1000 =  $\pm 10$   
1000~ =  $\pm 25$

SCALE 4 / 1  
REV -  
UNIT M/M

TITLE  
FME PLUG CRIMP FOR  
BULKHEAD CABLE RG/316U

DRAWING NO. FME15G-316

科曼實業有限公司  
**inter-con** enterprise

CHECKED  
11/20/2006  
DATE  
DRAWN  
11/20/2006  
DATE