



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER JIS H3250 C3604 BD.
 2. INSULATOR: PTFE ASTM-D-1457.
 3. NICKEL PL. 100 MIN. OVER NICKEL PL. 50 MIN.
 4. GOLD PL. 3 MIN. OVER COPPER PL. 50 MIN. OVER COPPER PL. 50 MIN.

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	PART NO.
6	HEX NUT	NOTE 1	NOTE 3	1	FME15SR-316-6
5	WASHER	NOTE 1	NOTE 3	1	FME15SR-316-5
4	FERRULE	NOTE 1	NOTE 3	1	N45-316-5
3	CONTACT PIN	NOTE 1	NOTE 4	1	FME15-179-3
2	INSULATOR	NOTE 2		1	FME15-179-2
1	BODY	NOTE 1	NOTE 3	1	FME15SR-316-1

DIMENSION ARE MILLIMETERS

UNLESS OTHERWISE SPECIFIED

TOLERANCES

1-10 = ±0.2

10-30 = ±0.4

30-200 = ±1.5

200-1000 = ±10

1000-~ = ±25

SCALE 4 / 1

REV -

UNIT M/M

TITLE

FME PLUG CRIMP FOR
BULKHEAD CABLE RG/316U

科曼實業有限公司
interconn enterprise

CHECKED

07/20/2009

DATE

DRAWN

FME15SR-316

07/20/2009

DATE