



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER JIS H3250 C3604BD.
2. P.BRONZE PER JIS H3270 C5441B-H.
3. GOLD PL. 3 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.
4. GOLD PL. 5 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	PART NO.
5	FERRULE	NOTE 1	NOTE 3	1	FERRULE-316U
4	CONTACT	NOTE 1	NOTE 4	1	MCX11-316-4
3	INSULATOR	TEFLON		1	MCX11-316-3
2	BODY	NOTE 1	NOTE 3	1	MCX11-316-2
1	BODY	NOTE 2	NOTE 3	1	MCX11-316-1

DIMENSION ARE MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 1-10 = ± 0.2 10-30 = ± 0.4 30-200 = ± 1.5 200-1000 = ± 1.0 1000-~ = ± 2.5		SCALE 5 / 1	REV -	UNIT M/M
TITLE MCX CRIMP PLUG RG/174U RG/316U		DRAWING NO. MCX11-316		
CHECKED Inter-con 科曼實業有限公司 enterprise		DRAWN 05/18/2010	DATE 05/18/2010	DATE 02/13/2004