



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER JIS H3250 C3604BD.
2. P.BRONZE PER JIS H3270 C5441B-H.
3. GOLD PL. 3 MIN. OVER NICKEL PL. 50 MIN.

4. GOLD PL. 5 MIN. OVER NICKEL PL. 50 MIN.
- OVER COPPER PL. 50 MIN.
- OVER COPPER PL. 50 MIN.

7	COVER	NOTE 1	NOTE 3	1	M CX-11-316L-6	DIMENSION ARE MILLIMETERS	SCALE	6 / 1	REV	-	UNIT	MM	料安實業有限公司 <b>inter-con n enterprise</b>	09/ 02/ 2003 DATE	
6	INSULATOR	TEFLON		1	M CX11-316L-6	UNLESS OTHERWISE SPECIFIED	TITLE	M CX RG/174,316U CRIMP PLUG							CHECKED 09/ 02/ 2003 DATE
5	FERRULE	NOTE 1	NOTE 3	1	FERRULE-316	TOLERANCES	RIGHT ANGLE								
4	CONTER PIN	NOTE 1	NOTE 4	1	M CX11-316L-4	1-10 = ±0.2	DRAWING NO.	M CX11-316L							
3	INSULATOR	TEFLON		1	M CX11-316L-3	10-30 = ±0.4									DRAWN 09/ 02/ 2003 DATE
2	BODY	NOTE 1	NOTE 3	1	M CX11-316L-2	30-200 = ±1.5									
1	BODY	NOTE 2	NOTE 3	1	M CX11-316L-1	200-1000 = ±10									
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	PART NO.	1000-~ = ±25									DATE