

NOTES: FINISH (PLATING THICKNESS MICRO-INCHES)


- BRASS PER JIS H3250 C3604BD.
- NICKEL PL. 100 MIN. OVER COPPER PL. 50 MIN.
- GOLD PL. 5 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.

8	FERRULE	NOTE 1	NOTE 2	1	FERRULE-213
7	CENTER PIN	NOTE 1	NOTE 3	1	N11-L400-7
6	RETAINER RING	NOTE 1	NOTE 2	1	N11-6
5	GASKET	SILICONE		1	N11-5
4	CONTACT BODY	NOTE 1	NOTE 2	1	N11-4
3	INSULATOR	PTFE		1	N11-L400-3
2	BODY	NOTE 1	NOTE 2	1	N11-L400-2
1	SHELL	NOTE 1	NOTE 2	1	N11-SHELL-A
NO.	DESCRIPTION	MATERIAL	FINISH	QTY	PART NO.

DIMENSION ARE MILLIMETERS  
UNLESS OTHERWISE SPECIFIED  
TOLERANCES

1-10 = ±0.2  
10-30 = ±0.4  
30-200 = ±1.5  
200-1000 = ±1.0  
1000-~ = ±2.5

SCALE	3 / 1	REV	-	UNIT	M/M
TITLE	N PLUG CRIMP CABLE 9913, LMR400				
DRAWING NO.	N11-L400				


 科曼實業有限公司  
**Inter-conn enterprise**

CHECKED: 03/30/2009 DATE: 03/30/2009

DRAWN: 03/30/2009 DATE: 03/30/2009