



- NOTES: FINISH (PLATING THICKNESS MICRO-INCHES)
1. BRASS PER JIS H3250 C3604BD.
 2. PTFE: ASTM-D-1475.
 3. SILICONE RUBBER: ASTM-E-1418PST.
 4. NICKEL PL. 100 MIN. OVER COPPER PL. 50 MIN.
 5. GOLD PL. 3 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.

11	HEX NUT	NOTE 1	NOTE 4	1	BNC18-59-13
10	WASHER	NOTE 1	NOTE 4	1	BNC18-58-12
9	GASKET	NOTE 3		1	BNC18-58-11
8	BRAID CLAMP	NOTE 1	NOTE 4	1	BNC18-59-10
7	CENTER PIN	NOTE 1	NOTE 5	1	N18-58-7
6	RETAINER RING	NOTE 1	NOTE 4	1	N11-RINGA
5	GASKET	NOTE 3		1	N11-GASKET
4	CONTACT BODY	NOTE 1	NOTE 4	1	N11-4
3	INSULATOR	NOTE 2		1	N18-58-3
2	CLAMP BODY	NOTE 1	NOTE 4	1	N18-58-2
1	SHELL	NOTE 1	NOTE 4	1	N11-SHELL-A
NO.	DESCRIPTION	MATERL.	FINISH	QTY	PART NO.

DIMENSION ARE MILLIMETERS
UNLESS OTHERWISE SPECIFIED
TOLERANCES

1-10 = ± 0.2
10-30 = ± 0.4
30-200 = ± 1.5
200-1000 = ± 10
1000-- = ± 25

SCALE 3 / 1 REV - UNIT M/M

TITLE
N PLUG RIGHT ANGLE
CRIMP CABLE LMR300

DRAWING NO. N18-L300

科曼實業有限公司
interconn enterprise

CHECKED
06/25/2013
DATE

DRAWN
06/25/2013
DATE