



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER JIS H3250 C3604 BD.
2. PHOSPHOR BRONZE PER JIS H3270 C5441B-H.
3. NICKEL PL. 100 MIN. OVER COPPER PL. 50 MIN.
4. GOLD PL. 3 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 30 MIN.

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	PART NO.
8	HEX NUT	NOTE 1	NOTE 3	1	N45-8
7	LOCK WASHER	NOTE 1	NOTE 3	1	N45-7
6	GASKET	SILICONE		1	N45-6
5	FERRULE	NOTE 1	NOTE 3	1	N45-316-5
4	CRIMP BODY	NOTE 1	NOTE 3	1	N45-316-4
3	CONTACT PIN	NOTE 2	NOTE 4	1	N45-316-3
2	INSULATOR	PTFE		1	N45-316-2
1	BODY	NOTE 1	NOTE 3	1	N45D-316-1

DIMENSION ARE MILLIMETERS	
UNLESS OTHERWISE SPECIFIED	
TOLERANCES	
1-10 = ± 0.2	
10-30 = ± 0.4	
30-200 = ± 1.5	
200-1000 = ± 10	
1000-~ = ± 25	

TITLE	SCALE	REV	UNIT
N BULKHEAD CRIMP JACK CABLE RG/178, 316U	3 / 1	-	M/M

科曼實業有限公司
inter-conm enterprise

DRAWN	CHECKED
DATE	DATE
12/ 10/ 2012	12/ 10/ 2012
DRAWN	DATE
12/ 10/ 2012	DATE