


- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER JIS H3250 C3604BD.
  2. BERYLLIUM COPPER QQ-C-530.
  3. GOLD PL. 5 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.
  4. GOLD PL. 15 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.
  5. NICKEL PL. 100 MIN. OVER COPPER PL. 50 MIN.

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	PART NO.
6	RENNBER RING	NOTE 2	NOTE 5	1	SMA-RING
5	GASKET	SILICONE		1	SMA-GSKET
4	CONTACT PIN	NOTE 1	NOTE 4	1	SMA11-086-4
3	INSULATOR	TEFLON		1	SMA11-316-3
2	BODY	NOTE 1	NOTE 3	1	SMA11-086-2
1	SHELL	NOTE 1	NOTE 3	1	SMA-SHELL

DIMENSION ARE: MILLIMETERS	
UNLESS OTHERWISE SPECIFIED	
TOLERANCES	
1-10	= ±0.2
10-30	= ±0.4
30-200	= ±1.5
200-1000	= ±10
1000-~	= ±25

SCALE	REV	UNIT
4 / 1	-	M/M
TITLE		
SMA CABLE SOLDER PLUG		
DRAWING NO.		
SMA11-086		

	CHECKED	DATE
		10/01/2008
DRAWN	DATE	
	10/01/2008	