



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER JIS H3250 C3604BD.
  2. BERYLLIUM COPPER QQ-C-530.
  3. GOLD PL. 5 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.
  4. GOLD PL. 15 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.
  5. NICKEL PL. 100 MIN. OVER COPPER PL. 50 MIN.

7	FERRULE	NOTE 1	NOTE 3	1	FERRULE-316
6	RENBER RING	NOTE 2	NOTE 5	1	SMA-RING
5	GASKET	SILICONE		1	SMA-GSKET
4	CONTACT PIN	NOTE 1	NOTE 4	1	SMA11-316-4
3	INSULATOR	TEFLON		1	SMA11-316-3
2	BODY	NOTE 1	NOTE 3	1	SMA11-316-2
1	SHELL	NOTE 1	NOTE 3	1	SMA-SHELL
NO.	DESCRIPTION	MATERIAL	FINISH	QTY	PART NO.

DIMENSION ARE: MILLIMETERS

UNLESS OTHERWISE SPECIFIED TOLERANCES

- 1-10 = ±0.2
- 10-30 = ±0.4
- 30-200 = ±1.5
- 200-1000 = ±10
- 1000-~ = ±25

SCALE

4 / 1

REV

-

UNIT

M/M

TITLE

SMA CABLE CRIMP PLUG

科曼實業有限公司  
interconn enterprise

CHECKED

01/01/2004 DATE

DRAWING NO.

SMA11-316

DRAWN

01/01/2004 DATE