



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER JIS H3250 C3604BD.
  2. PTFE: ASTM-D-1457.
  3. GOLD PL. 1-2 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.
  4. GOLD PL. 3 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.

7	FERRULE	NOTE 1	NOTE 3	1	SMA45MW-178-5
6	RENNER RING	NOTE 1		1	SMA-RING
5	GASKET	SILICONE		1	SMA-GSKET
4	CONTACT PIN	NOTE 1	NOTE 4	1	SMA11MW-178-4
3	INSULATOR	NOTE 2		1	SMA11-316-3
2	BODY	NOTE 1	NOTE 3	1	SMA11MW-178-2
1	SHELL	NOTE 1	NOTE 3	1	SMA-SHELL
NO.	DESCRIPTION	MATERIAL	FINISH	QTY	PART NO.

DIMENSION ARE MILLIMETERS	
UNLESS OTHERWISE SPECIFIED	
TOLERANCES	
1-10 = ±0.2	
10-30 = ±0.4	
30-200 = ±1.5	
200-1000 = ±10	
1000~ = ±25	

SCALE	4 / 1	REV	-	UNIT	M/M
TITLE	SMA CABLE CRIMP PLUG				
DRAWING NO.	SMA11MW-178				

	CHECKED	04/02/2010	DATE
	DRAWN	04/02/2010	DATE