



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER JIS H3250 C3604BD.
2. BERYLLIUM COPPER QQ-C-530. HEAT TREAT TO 315°C FOR 2 HOURS.

3. GOLD PL. 5 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.
4. GOLD PL. 15 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.
5. NICKEL PL. 100 MIN. OVER COPPER PL. 50 MIN.

9	NUT	NOTE 1	NOTE 3	1	SMA11-316L-9
8	INSULATOR	TEFLON		1	MCX11-316L-6
7	FERRULE	NOTE 1	NOTE 3	1	FERRULE-316
6	RETAINER RING	NOTE 2	NOTE 5	1	SMB11-RING
5	CENTRACT PIN	NOTE 2	NOTE 4	1	SMB11-316L-5
4	INSULATOR	TEFLON		1	SMB11-316L-4
3	BODY	NOTE 1	NOTE 3	1	SMB11-316L-3
2	BARREL	NOTE 1	NOTE 3	1	SMB11-316L-2
1	SHELL	NOTE 1	NOTE 3	1	SMB11-316L-1
NO.	DESCRIPTION	MATERIL	FINISH	Q'TY	PART NO.

DIMENSION ARE MILLIMETERS
UNLESS OTHERWISE SPECIFIED
TOLERANCES

1-10 = ±0.2
10-30 = ±0.4
30-200 = ±1.5
200-1000 = ±1.0
1000-~ = ±2.5

SCALE	4 / 1	REV	-	UNIT	M/M
TITLE	SMB CRIMP PLUG RIGHT ANGLE				
DRAWING NO.	SMB11-316L				

CHECKED	 科曼實業有限公司 interconn enterprise	
DRAWN		
DATE	11 / 11 / 2008	DATE
DATE	11 / 11 / 2008	DATE