



- NOTES: FINISH (PLATING THICKNESS ALLOY-INCHES)
1. BRASS PER JIS H3250 C3604BD.
 2. P.BRONZE PER JIS H3270 C5441B-H.
 3. GOLD PL 1-2 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.
 4. GOLD PL 3 MIN. OVER NICKEL PL. 50 MIN. OVER COPPER PL. 50 MIN.

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	PART NO.
5	FERRULE	NOTE 1	NOTE 3	1	FERRULE-316
4	CONTACT PIN	NOTE 2	NOTE 4	1	SMB11-316-4
3	INSULATOR	PTFE		1	SMB11-316-3
2	BODY	NOTE 1	NOTE 3	1	SMC11-316-2
1	HEX SHELL	NOTE 1	NOTE 3	1	SMC11-SHELL

DIMENSION ARE MILLIMETERS
UNLESS OTHERWISE SPECIFIED
TOLERANCES

1-10 = ± 0.2
10-30 = ± 0.4
30-200 = ± 1.5
200-1000 = ± 10
1000~ = ± 25

SCALE 4 / 1
REV -
UNIT M/M

TITLE
SMC CRIMP PLUG RG/174U, 316U

DRAWING NO.

SMC11-316

科曼實業有限公司
Inter-conm enterprise

CHECKED

DRAWN

10/07/2014 DATE

10/07/2014 DATE