

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER JIS H3250 C3604BD.
2. INSULATOR: PTFE ASTM-D-1457.
3. BERYLLIUM COPPER QQ-C-530.
- HEAT TREAT TO 315°C FOR 2 HOURS.
4. GOLD PL. 3 MIN. OVER NICKEL PL. 50 MIN.

5. OVER COPPER PL. 50 MIN.
6. GOLD PL. 15 MIN. OVER NICKEL PL. 50 MIN.
7. OVER COPPER PL. 50 MIN.
8. NICKEL PL. 100 MIN. OVER COPPER PL. 50 MIN.
9. FREQUENCY RANGE: DC UP 4 GHz.
10. VSWR: 1GHz 1.15, 2.5GHz 1.25, 4GHz 1.38.

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	PART NO.
8	COVER	NOTE 1	NOTE 4	1	SMZ-COVER
7	FERRULE	NOTE 1	NOTE 4	1	FERRULE-195
6	RETAINER RING	NOTE 3	NOTE 6	1	SMZ11-RING
5	BARREL BODY	NOTE 1	NOTE 4	1	SMZ11L-195-5
4	CONTACT PIN	NOTE 3	NOTE 5	1	SMZ11L-179-4
3	INSULATOR	NOTE 2		1	SMZ19-75-3
2	BODY	NOTE 1	NOTE 4	1	SMZ11L-179-2
1	SHELL	NOTE 1	NOTE 4	1	SMZ11L-179-1


DIMENSION ARE MILLIMETERS
UNLESS OTHERWISE SPECIFIED
TOLERANCES

1-10 = ±0.2
10-30 = ±0.4
30-200 = ±1.5
200-1000 = ±10
1000~ = ±25

SCALE	REV	UNIT
4 / 1	-	M/M

TITLE
SMZ PLUG RIGHT ANGLE CRIMP
RG/180U, RG/195U

DRAWING NO. SMZ11L-195

CHECKED	DRAWN
 科曼實業有限公司 Inter-conn enterprise	05/ 23/ 2014 DATE
05/ 22/ 2014 DATE	